



ZERUST® ZerioGuard® 8

Technical Data Sheet

Product Description

ZERUST® ZerioGuard® 8 is a water-soluble corrosion inhibitor powder specifically designed to protect pipelines during hydrostatic testing. This critical process verifies structural integrity but often introduces challenges such as corrosion caused by delays, residual water pockets after draining, or the use of low-quality water.

ZerioGuard® 8 helps mitigate these risks by preventing corrosion before it starts, reducing operational delays, minimizing costs, and safeguarding pipeline integrity. By streamlining hydrotesting operations, it supports a more efficient and environmentally* responsible approach to pipeline preservation.

*Consult local environmental regulations to ensure compliance with specific discharge requirements in the local area.

Typical Applications

- Hydrostatic testing of pipelines, piping circuits
- Use in facilities requiring environmentally friendly corrosion inhibitors.
- Testing applications in regions with strict hydrotest discharge regulations (e.g., California), where its near-neutral chemistry may facilitate regulatory compliance.

Key Advantages


- Corrosion Reduction: Protects assets during hydrostatic testing, especially during downtime between testing and commissioning.
- Environmental Compliance: Its neutral pH may make the product safer for discharge onto the soil, potentially reducing the need for additional steps to comply with local environmental regulations, subject to proper evaluation.
- Cost-Effective: Reduces potential repair costs by minimizing corrosion damage.
- Ease of Use: Water-soluble powder dissolves easily, simplifying application.
- Operational Efficiency: Helps maintain pipeline integrity, reducing delays and operational risks.
- Versatility: Suitable for various water qualities and diverse hydrotesting scenarios.

Operating Summary

- Mix ZerioGuard® 8 thoroughly into water. Concentration depends on length of time the asset will be in contact with the solution, condition of the asset, and quality of the water.**
- Apply solution to asset as specified in the Scope of Work. A ZERUST® Field Engineer can be assigned to oversee the operation.
- Dispose of the solution in accordance with local, regional, national, and international regulations as applicable.

**Consult a ZERUST® representative to discuss specific needs.

Scan QR for more



product information

ZERUST® ZerioGuard® 8

Technical Data Sheet

Typical Properties

Properties***	Details
Appearance	White powder
Substrate	Ferrous
pH	6.5 - 7.5 (1% in water)

***Typical values are not meant to be a specification.

Availability

Contact a ZERUST® representative for ordering information.

Product Number	Unit of Measure****
460-F-00023PL	33 lb (15 kg) pail
460-F-00023SS	1,000 lb (454 kg) super sack (Made To Order)

****Product sold in US customary units. Metric units approximate.

Storage

Store in original packaging in a cool, dry place away from sunlight; keep tightly closed for a shelf life of 36 months, unopened.


† DECLARATION

Corrosion protection claims are based on Northern Technologies International Corporation (NTIC) internal laboratory testing performed under controlled parameters on contaminate-free substrates. Real-world application corrosion protection duration on different substrates will vary and depends on factors such as, but not limited to, the application or use, environmental/ storage conditions, surface cleanliness, type of substrates, and coating thickness (where applicable). The use of the term "Up to" in reference to time is defined as any time duration from zero up to a specified time frame, but in no event beyond the specified time frame. The use of the term "for years" is based on NTIC's experience with its products but is in no way guaranteed. The use of the term "Up to" in reference to volume is defined as any volume from zero up to a specified volume but in no event beyond the specified volume of protection. It is the customer's/user's obligation to evaluate product performance, corrosion protection duration, safety, and suitability for intended use within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY/DISCLAIMER Warranty is limited to the replacement of a product that fails to meet specifications. For full warranty and disclaimer information, visit www.zerust.com/warranty.

©2013-2026 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak, Cor Tab, EXCOR®, Flange Saver, ICT®, Natur-VC®, NTIO, Plastabs, Z-CISO, Zerion, ZERUST®, 5alf-111i, Z-PAK0 and the Color "Yellow", ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us



Scan QR Code

A product of:
 Northern Technologies
 International Corp
 4201 Woodland Road
 Circle Pines, MN 55014 USA
 Toll-Free: +1 (800) 328-2433
www.ZerustIS.com

Supersedes: v4
 Revised: 07/06/2026



With over 50 years of experience, ZERUST Integrity Solutions®, a division of Northern Technologies International Corporation (NTIC), creates unique inhibitor-based corrosion prevention solutions to serve terminals, pipelines, exploration and production, equipment suppliers, transportation sectors, and more.

ZERUST Integrity Solutions®, ZERUST®/EXCOR®, and Natur-Tec® are sister companies under NTIC.

