



ZERUST® Zerion™ FAN-6

Technical Data Sheet

Product Description

ZERUST® Zerion™ FAN-6 is a non-hazardous, environmentally friendly soluble corrosion inhibitor (SCI) powder engineered for corrosion protection in aggressive environments. It is especially well-suited for use under storage tanks, where its more alkaline pH range helps mitigate corrosive and acidic species. ZERUST® Zerion™ FAN-6 can be used to supplement volatile/vapor corrosion inhibitors (VCIs) to provide additional coverage. It is also ideal for use as a top dressing as it can be welded over.

In addition to tank applications, ZERUST® Zerion™ FAN-6 is effective for pipeline preservation, bulk water lay-up, fire water protection, and rinse water to reduce flash corrosion. It offers versatile, economical, and long-term corrosion protection for both immersion and rinse applications.

Typical Applications

- Under-tank environments
- Tank internals protection
- Pipeline preservation
- Bulk water lay-up
- Fire water systems
- Rinse water corrosion control
- Temporary system shutdowns
- Hydrostatic testing
- Sprinkler system lay-up
- Welding operations

Key Advantages

- Neutralizes acidic species and creates an alkaline environment
- Provides long-term corrosion protection
- Effective at low concentrations (0.5%–10%), depending on water quality, performance needs, and lay-up duration
- Suitable for both immersion and rinse applications
- Compatible with potable water and can be combined with VCIs for extended airspace protection
- Non-hazardous and environmentally friendly, ensuring sustainable corrosion protection
- Economical solution for a wide range of applications
- Withstands high-temperature environments: Suitable for top dressing applications, including use around asphalt tanks and welding areas, without requiring removal.


Application Guidelines and Removal*

General Use: Use ZERUST® Zerion™ FAN-6 at concentrations ranging from 0.5% to 10%, depending on the quality of the water, the desired level of corrosion protection, and the expected duration of lay-up.

Under-Tank Application: ZERUST® Zerion™ FAN-6 can be used at higher concentrations within this range to enhance alkalinity and combat acidic or corrosive conditions often found in tank pad environments.

*Consult a ZERUST® representative to discuss specific needs.

Scan QR for more



product information

ZERUST® Zerion™ FAN-6

Technical Data Sheet

Typical Properties

Properties**	Details
Appearance	White powder
Substrate	Ferrous
pH	10.5 - 11.5

**Typical values are not meant to be a specification.

Availability

Contact a ZERUST® representative for ordering information.

Product Number	Unit of Measure***
460-F-00015	40 lbs (18.14 kg) pail
460-F-00015SS	2000 lbs (907.1 kg) super sack

***Product sold in US customary units. Metric units approximate.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place

† DECLARATION

Corrosion protection claims are based on Northern Technologies International Corporation (NTIC) internal laboratory testing performed under controlled parameters on contaminate-free substrates. Real-world application corrosion protection duration on different substrates will vary and depends on factors such as, but not limited to, the application or use, environmental/ storage conditions, surface cleanliness, type of substrates, and coating thickness (where applicable). The use of the term "Up to" in reference to time is defined as any time duration from zero up to a specified time frame, but in no event beyond the specified time frame. The use of the term "for years" is based on NTIC's experience with its products but is in no way guaranteed. The use of the term "Up to" in reference to volume is defined as any volume from zero up to a specified volume but in no event beyond the specified volume of protection. It is the customer's/user's obligation to evaluate product performance, corrosion protection duration, safety, and suitability for intended use within the scope advised in the data sheet and to comply with all applicable laws and regulations.

LIMITED WARRANTY/DISCLAIMER Warranty is limited to the replacement of a product that fails to meet specifications. For full warranty and disclaimer information, visit www.zerust.com/warranty.

©2013-2025 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak, Cor Tab, EXCOR®, Flange Saver, ICT®, Natur-VCI®, NTIO, Plastabs, Z-CISO, Zerion, ZERUST®, 5alf-111i, Z-PAKO and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

Contact Us



Scan QR Code

A product of:
 Northern Technologies
 International Corp
 4201 Woodland Road
 Circle Pines, MN 55014 USA
 Toll-Free: +1 (800) 328-2433
www.ZerustIS.com

Supersedes: v3
 Revised: 05/08/2025



With over 50 years of experience, ZERUST® Integrity Solutions, a division of Northern Technologies International Corporation (NTIC), creates unique inhibitor-based corrosion prevention solutions to serve terminals, pipelines, exploration and production, equipment suppliers, transportation sectors, and more.

ZERUST® Integrity Solutions, ZERUST®/EXCOR®, and Natur-Tec® are sister companies under NTIC.

